



TBEN | TBDP | IP67 Block I/O Modules





For Ethernet and PROFIBUS

Turck has a new generation of block I/O modules with extended temperature range from -40...+70 °C. The module series TBEN (Ethernet) and TBDP (PROFIBUS-DP) can also be used in climates and applications, in which nearly all other I/O modules capitulate. Thanks to PROFINET MRP and EtherNet/IP™ DLR, the new Ethernet protocol functions, you can now increase the fieldbus availablity. In addition, the modules support Fast Start-Up (FSU) and QuickConnect (QC).

The block I/Os are as their predecessors incorporated in a rugged, highly protection rated housing. Thanks to the multiprotocol function configuration is easy: Once connected, the modules run automatically without user intervention in PROFINET, EtherNet/IP™ and Modbus TCP networks.

The devices with digital output of both series can switch 2 A. This allows you to reduce the inventory of types with different output currents. All devices also support common grounding without the need for complicated modifications to the I/O module. By using ARGEE, TBENs can also be deployed as self-contained field logic controllers (FLC). This enables independent application directly in the block-I/O to control and perform arithmetic, timer, counter and binary switch functions as well as exchange of data with higher level controls.

Advantages

- Automated operation in PROFINET, EtherNet/IP™ and Modbus TCP networks
- Broadly applicable thanks to wide temperature range
- Easily mounted
- TBEN programmable with ARGEE/FLC



IP67 Block I/O Modules

Proven features

- High-quality housing
 - resistant to vibrations and deformation
- high protection class IP65/IP67/IP69K
- Easy to configure with configuration files
- Web server for additional diagnosis
- Ethernet multiprotocol technology for Modbus TCP, EtherNet/IP™, PROFINET automatic protocol recognition at startup
- Integrated switch supports Ethernet line topology
- Protocol functions:
 PROFINET: Fast Start-Up (FSU)
 EtherNet/IP™: QuickConnect (QC)

New features

- Extended temperature range
 - -40...+70 °C
- Improved design, easily mounted
- All outputs can switch up to 2 A even the universal I/O
- Improved grounding concept: Fieldbus and I/O-part are separable
- New protocol functions: PROFINET: Media Redundancy (MRP) EtherNet/IP™: Device Level Ring (DLR)
- TBEN programmable with ARGEE/FLC

PROFIBUS

TBDP	Type code	ID number	Description
	TBDP-L2-16DIP	6814001	IP67 block I/O module with 16 digital inputs
active the last of	TBDP-L2-8DIP-8DOP	6814002	IP67 block I/O module with 8 digital inputs and 8 digital outputs
E P. P. P. P.	TBDP-L2-16DOP	6814003	IP67 block I/O module with 16 digital outputs
	TBDP-L2-16DXP	6814004	IP67 block I/O module with 16 universal digital I/Os

Ethernet Multiprotokoll

TBEN	Type code	ID number	Description
	TBEN-L5-16DIP	6814085	IP67 block I/O module with 16 digital inputs
C C C C C C C C C C C C C C C C C C C	TBEN-L5-8DIP-8DOP	6814086	IP67 block I/O module with 8 digital inputs and 8 digital outputs
EN SHOW EN	TBEN-L5-16DOP	6814087	IP67 block I/O module with 16 digital outputs
	TBEN-L5-16DXP	6814088	IP67 block I/O module with 16 universal digital I/Os

